



# Mini 1



## Installation size and step



## Light scattering angle



## Technical information

Available colors: ○

Power 0,36W

Light flux 45 lm

|                     |            |
|---------------------|------------|
| Crystal type        | 2835       |
| Operating voltage   | 12V DC     |
| Glow temperature    | ○6500 K    |
| Scattering angle    | 120°       |
| Protection class    | IP 65      |
| Working temperature | -30 +50 °C |

A great solution for ultra thin letters and small signs. The dimensions are only 12.2\*10\*9mm. The chip of increased brightness gives a very good illumination of the sign, reduced energy consumption allows you to save on power supplies.

### Installation:

- 3D illumination of LED letters with a depth of 50-80 mm
- Light box 50-80 mm deep

### Features and benefits:

- Special polycarbonate lens with light transmission > 88%
- Maximum Tj temperature < 80°C
- Brightness drop <20% after 40,000 hours
- CRI greater than 70
- High level of protection Ip67
- Warranty 5 years

## Packaging information

| Packaging | In a chain | In the package | In a box  |
|-----------|------------|----------------|-----------|
| Number    | 20 PCS     | 1200 PCS       | 24000 PCS |
| Weight    | 0,04 kg    | 2.4 kg         | 48 kg     |



## Illumination table

| Installation depth | Installation step by centers of modules | Number per 1 m <sup>2</sup> | Power per 1 m <sup>2</sup> |
|--------------------|---|-----------------------------|----------------------------|
| 60 mm              | 60 mm                                   | 256 PCS                     | 92 W                       |
| 80 mm              | 100 mm                                  | 100 PCS                     | 36 W                       |